

eWON 2005 - Security LED

The eWON 2005 and 4005 types had a supplementary security LED. On the 2005CD (4005CD) versions this LED has been removed.

The following scenario exists for this led.



The scenario depends only on the eWON configuration:

Scenario	Description
OFF	Allow all traffic is selected
Blink 1 sec. Green 1 sec. OFF	Discard all but VPN and initiate or Discard all but VPN and initiate and PING
Solid Green	WAN interface is not connected



Revision

Revision History

Revision Level	Date	Description
1.0	25/01/2010	Creation of document

Document build number: 6

Note concerning the warranty and the rights of ownership:

The information contained in this document is subject to modification without notice. Check <http://wiki.ewon.biz> for the latest documents releases.

The vendor and the authors of this manual are not liable for the errors it may contain, nor for their eventual consequences.

No liability or warranty, explicit or implicit, is made concerning the quality, the accuracy and the correctness of the information contained in this document. In no case the manufacturer's responsibility could be called for direct, indirect, accidental or other damage occurring from any defect of the product or errors coming from this document.

The product names are mentioned in this manual for information purposes only. The trade marks and the product names or marks contained in this document are the property of their respective owners.

This document contains materials protected by the International Copyright Laws. All reproduction rights are reserved. No part of this handbook can be reproduced, transmitted or copied in any way without written consent from the manufacturer and/or the authors of this handbook.

eWON sa, Member of ACT'L Group