

# Parse a file

## 1. Purpose

The script example shown below permit parse a file, in this exemple we use estat.htm to analise and we extract the information below.

**Gsm IMEI**: The International Mobile Equipment Identity is a number, usually unique, to identify GSM . The IMEI number is used by a GSM network to identify valid devices and therefore can be used for stopping a stolen phone from accessing that network.

**GSM IMSI**: An International Mobile Subscriber Identity is a unique identification associated with all GSM,UMTS and LTE network mobile phone users.

**Gsm CillID**: is a generally unique number used to identify each Base tranceiver station (BTS) or sector of a BTS within a location area code (LAC) if not within a GSM network.

**Gsm LAC**: local area code.

### 2. Implementation

Put the following code into a User Section of the Basic Script in eWON.

```
GSM Info:
Close 1
OPEN "exp:$dtES $ftT" FOR TEXT INPUT AS 1
Loop:
A\$ = Get 1
IF A$<>"" THEN
  I% = INSTR 1,A$,"GsmIMEI"
  IF I\% = 1 THEN PRINT A\%
  J% = INSTR 1,A$, "GsmIMSI"
  IF J_{\%}^{\%} = 1 Then print A_{\%}^{\%}
  K% = INSTR 1,A$, "GsmCellId"
  IF K% = 1 THEN PRINT A$
  L = INSTR 1, A$, "GsmLAC"
  IF L% = 1 THEN PRINT A$
EndIf
If A$ <>"" Then GOTO Loop
Close 1
End
```

We use the "exp:\$dtES \$ftT" to load information from "estat.htm" where GsmIMEI, GsmINSI, GsmCellId & GsmLAC are located.



#### **Knowledge Base**

KB-0148-00 / Rev. 1.0

GsmSigna1:20
GsmBars:5
GsmNetReg:1
GsmNetRegTxt:Home network (EDGE)
GsmWlessNet:2
GsmNbOp:3
GsmOperList:[{"opna":"PROXIMUS ","opid":" 20601","stat":"="},{"opna":"E
GsmOpName:PROXIMUS
GsmOpId:20601
GsmOpStat:=
GsmCellId:46383
GsmLAC:7131
RxPwr:-73
GsmBand:0
GsmCfgWlessNet:0
GsmIMEI:351579051143814
GsmIMSI:206012215837299
GsmCCID:8932002100145923522

"I% = INSTR 1,A,"GsmIMEI"" is use as a filter to extract from "estat.htm" file only the value we want, in this case GsmIMEI

With the result below :

Script Control				
S 1 GsmCellId:46383				
GsmLAC:7131				
GsmIMEI:351579051143814				
GsmIMSI:206012215837299				
Update Output	Script starts at eWON Boot 📮 Update Autorun mode			
Execute Command				

## Revision

### **Revision History**

Revision Level	Date	Description
1.0	13/09/2012	Creation of document

#### Document build number: 13

#### Note concerning the warranty and the rights of ownership:

The information contained in this document is subject to modification without notice. Check http://wiki.ewon.biz for the latest documents releases.

The vendor and the authors of this manual are not liable for the errors it may contain, nor for their eventual consequences.

No liability or warranty, explicit or implicit, is made concerning the quality, the accuracy and the correctness of the information contained in this document. In no case the manufacturer's responsibility could be called for direct, indirect, accidental or other damage occurring from any defect of the product of errors coming from this document.

The product names are mentioned in this manual for information purposes only. The trade marks and the product names or marks contained in this document are the property of their respective owners.

This document contains materials protected by the International Copyright Laws. All reproduction rights are reserved. No part of this handbook can be reproduced, transmitted or copied in any way without written consent from the manufacturer and/or the authors of this handbook.

eWON sa, Member of ACT'L Group